
NASA TECH BRIEF



This NASA Tech Brief is issued by the Technology Utilization Division to acquaint industry with the technical content of an innovation derived from the NASA space program.

Nylon Sleeve for Cavity Amplifier Holds Tuning Despite Heat



The problem: Detuning of cavity amplifiers with change in temperature. This results in deterioration of the performance of the amplifier at its design frequency. In cavity amplifiers and filters it is desirable that constant performance be maintained regardless of thermal changes. These changes often cause an "off resonance shift" in a cavity filter and a deterioration of performance in a cavity amplifier

The solution: Mount the tuning probe in a nylon sleeve. Thermal expansion and contraction of the nylon nullifies unwanted capacitive and inductive changes in the resonant elements.

How it's done: A nylon sleeve is fitted between the tuning probe and the threaded bushing in which it is mounted. The sleeve is tapped to permit adjustment of the threaded probe for proper tuning. The nylon has a higher thermal expansion ratio than the surrounding metal of the compensator housing.

As the temperature rises, the nylon expands and carries the tuning probe away from the plate line. This action maintains the desired negative characteristic of the capacity of the tuning probe as related to the plate line.

The composite tuning probe with nylon sleeve reacts to temperature changes so that unwanted reactive changes are nullified. It can be adjusted to resonate the cavity either as the main tuning adjustment or as the compensating element. This innovation provides for excellent performance with respect to cost of the parts and construction.

Notes:

 Application of this invention appears to be limited to cavity amplifiers and filters, but the principle of automatic temperature compensation by means of a nylon member that expands with an increase in temperature could be adapted to other electronic devices that require temperature compensation.

(continued overleaf)

This document was prepared under the sponsorship of the National Aeronautics and Space Administration. Neither the United States Government, nor NASA, nor any person acting on behalf of NASA: A. Makes any warranty or representation, express or implied, with respect to the accuracy, completeness, or usefulness of the information contained in

this document, or that the use of any information, apparatus, method, or process disclosed in this document may not infringe privately-owned rights; or B. Assumes any liabilities with respect to the use of, or for damages resulting from the use of, any information, apparatus, method, or process disclosed in this document.

2. For further information about this innovation inquiries may be directed to:

Technology Utilization Officer Jet Propulsion Laboratory 4800 Oak Grove Drive Pasadena, California 91103

Reference: B63-10179

Patent status: NASA encourages the immediate commercial use of this invention. It is owned by

NASA and a patent application has been filed. When patented, royalty-free, nonexclusive licenses for its commercial use will be available. Inquiries concerning license rights should be made to NASA Headquarters, Washington, D.C., 20546.

Source: Lloyd Derr

(JPL-255)